


Balfit[®] SAE 37° Flared Pipe Fittings

Balfit® JIC x SAE-ORB Straight Male Connector - 35.220.

carbon steel JIC x SAE-ORB straight male connector



According to ISO 8434-2 According to SAE J514

Material: Carbon Steel Finish: Zinc-plated

part number	Ø tube		thread		dimensions				working pressure
	mm	inch	R1	R2	В	C1	C2	Н	bar
35.220.0404	6	1/4"	7/16" – 20	7/16" – 20	31	14	9	14	345
35.220.0405	6	1/4"	7/16" - 20	1/2" - 20	31	14	9	16	345
35.220.0406	6	1/4"	7/16" - 20	9/16" – 18	33	44	10	17	345
35.220.0505	8	5/16"	1/2" - 20	1/2" - 20	31	14	9	16	345
35.220.0606	10	3/8"	9/16" - 18	9/16" - 18	33	14	10	17	345
35.220.0608	10	3/8"	9/16" - 18	3/4" - 16	35	14	11	22	310
35.220.0808	12	1/2"	3/4" - 16	3/4" - 16	38	17	11	22	310
35.220.0810	12	1/2"	3/4" - 16	7/8" – 14	41	17	13	27	240
35.220.1008	14	5/8"	7/8" - 14	3/4" - 16	41	19	11	24	240
35.220.1010	15	5/8"	7/8" – 14	7/8" – 14	43	19	13	27	240
35.220.1012	16	5/8"	7/8" - 14	1.1/16" - 12	47	19	15	32	240
35.220.1210	20	3/4"	1.1/16" - 12	7/8" – 14	46	22	13	27	240
35.220.1212	20	3/4"	1.1/16" - 12	1.1/16" - 12	50	22	15	32	240
35.220.1216	20	3/4"	1.1/16" - 12	1.5/16" - 12	51	22	15	38	210
35.220.1612	25	1"	1.5/16" - 12	1.1/16" - 12	51	23	15	36	210
35.220.1616	25	1"	1.5/16" - 12	1.5/16" - 12	52	23	15	38	210
35.220.2020	32	1.1/4"	1.5/8" - 12	1.5/8" - 12	55	24	15	50	170
35.220.2424	38	1.1/2"	1.7/8" - 12	1.7/8" - 12	60	28	15	55	140

also available:

Balfit® Stainless Steel Straight Male Connector JIC x SAE-ORB

(add an 'S' at the end of the part number; ex: 35.220.0808 S)

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.

Balflex® - The European Technology