


Balfit® SAE 37° Flared Pipe Fittings



Balfit® NPT Female x JIC Male Connector – 35.280.

carbon steel NPT female x JIC male straight connector



According to **ISO 8434-2** According to **SAE J514**

Material: Carbon Steel
Finish: Zinc-plated

part number	∅ tube		thread		dimensions		working pressure bar
	mm	inch	R1	R2	B	H	
35.280.0404	6	1/4"	1/4" – 18	7/16" – 20	32	14	345
35.280.0504	8	5/16"	1/4" – 18	1/2" – 20	32	17	345
35.280.0604	10	3/8"	1/4" – 18	9/16" – 18	34	17	345
35.280.0606	10	3/8"	3/8" – 18	9/16" – 18	34	19	275
35.280.0808	12	1/2"	1/2" – 14	3/4" – 16	41	22	210
35.280.1008	16	5/8"	1/2" – 14	7/8" – 14	42	24	210
35.280.1212	20	3/4"	3/4" – 14	1.1/16" – 12	44	27	170
35.280.1616	25	1"	1" – 11.1/2"	1.5/16" – 12	51	36	140

also available:

Balfit® Stainless Steel NPT Female x JIC Male Connector

(add an 'S' at the end of the part number; ex: 35.280.0404 S)

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.

Balflex® – The European Technology